Smart Payment Terminal

SUNMI P3



PCI PTS 6.2

isa payWave »))



AMERICAN



Big Screen, Powerful, Innovative Payment Terminal.







6.75" HD touchscreen, ultimate experience.

P3 adopts a metallic color design with a 6.75" HD display. The customer-facing NFC reader offers better tap-and-go experience.

Slim yet powerful, for seamless payments.

A quad-core processor and 2GB + 32GB memory are available to offer always smooth experience.

Cutting edge communication technologies like eSIM are supported for quick payment.

Equipped with a one-stop payment solution to ensure worry-free transaction.

SUNMI OS: designed for payment and PCI & EMV certified security. TMS: deployed on a private cloud to securely manage your devices. RKI: inject or update keys with lower operating costs. Remote Assistance: remote troubleshooting for better service experience.





All-rounder, in all payment scenarios.

Scan, tap, chip, swipe or customers can pay the way they like.












SUNMI P3 Smart Payment Terminal

^{*}These accessories will be launched to the market soon. Please consult sales for details.

SUNMI P3 Application Scenario







F&B

SUNMI P3 Tech Specs

General Configuration

Product Model

T6F10

os

SUNMI OS (*Android 11 Go)

Processor

Quad-core 4*A53 2.0GHz

Memory

2GB RAM + 32GB ROM

Display

6.75" TFT HD+ 720*1600, IPS Capacitive multi-touch

Camera

2MP FF Rear Optional: 5MP AF Rear Optional:2MP FF Front Support 1D/2D barcode scanning

IC Card

Smart IC card/logic encryption contact card; ISO 7816/EMV/PBOC 3.0 compliant; 5V/3V/1.8V

Magstripe Reader

1/2/3 track; Bi-directional card reading; ISO 7810/7811 compliant

NFC Reader

Type A&B card, MIFARE card, ISO/IEC 14443 and ISO 15693 compliant

Scanner

2D barcode scan engine (optional)

Printer

Built-in thermal printer Print speed: 80mm/s Paper roll width/diameter:

Network

2G & 3G & 4G

Wi-Fi

2.4GHz/5GHz IEEE 802.11 a/b/g/n/ac

Fingerprint

FAP10, FBI Certified (Optional)

GPS

GPS AGPS Beidou Glonass

Card Slot

2*PSAM 1*SIM+1*Micro SD/2*SIM MicroSD(TF) up to 128G

Speaker

I.OW

Battery

Removable lithium battery 7.7V / 2630mAh

Power Adapter

Input: AC 100 ~ 240V Output: DC 5V / 2A

Ports

1* Type-C 6* Pogo pin on the back for charging/communication(Optional)

Buttons

1*Power button, 1*Function button (optional)

Dimensions(L*W*H)

200mm*80mm*17mm

Total Weight

400g (include battery)

Environment

Operating temperature: -10°C~50°C Storage temperature: -20°C~70°C

Accessories

Multi-functional base Support charging & communication

^{1.}The usable memory may be less than the installed memory. 2.All specifications are subject to change without (prior) notice.